- Tracheostomy tube with two inner cannulas (IC) and CUFF
- Also available with suction line (REF 18932, on separate data sheet)
- Soft, flexible neck-flange with key tube identification data clearly marked
- With rotating 15 mm connector (VARIO) to buffer torque and tension caused by tractive forces from ventilation equipment
- With X-ray contrast stripe
- Set includes tube holder, obturator and product ID card
- Inner cannula also available separately (REF 18933), size to be selected according to the size of the TRACHEOTEC® PRO outer cannula





ethylene oxid Do not resterilize



Keep away from sunlight



Single patient use



Consult instructions for use



CAUTION: United States Federal law restricts this device to sale. distribution and use by or on order of a physician or a licensed practitioner (in the US only).



( **€0482** CE marking identification number of the notified body

## **Order information:**

TRACHEOTEC® PRO VARIO CUFF 2 IC, SIZE 6-10



When ordering, please state the size after the item number!

15mm	CUFF	BE	h	(EF	18922	_
		a	_		4000	

**REF 18933** 

Size	O.D. Neck Flange mm	O.D. Tip mm	I.D. mm	Length mm (Midline)	Length mm	REF
6	8.7	8.7	6.0	60.7	67.1	18922-06
7	10.0	10.0	7.0	69.6	77.0	18922-07
8	11.3	11.3	8.0	79.5	87.9	18922-08
9	12.7	12.7	9.0	85.5	94.9	18922-09
10	14.0	14.0	10.0	95.0	105.3	18922-10

O.D. Shield = outer diameter behind the neck flange · O.D. Tip = outer diameter at the tube tip · I.D. = inner diameter at the tip of the inner cannula · O-tube = outer cannula · I-tube = inner cannula Length = length over the outer curve · Length (midline) = length of centre line from neck flange to tip