## **DURATWIX® UNI-VARIO LINGO**

1 ICV + 1 ICFU

- Tracheostomy tube with two inner cannulas, both with 15 mm connector, one with rotating 15 mm swivel connector (ICV), the other one fenestrated (ICFU)
- Soft double-swivel ROTATWIX® neckflange, rotating in 360° for enhanced neck mobility
- ► With ASPILO® sieve-fenestration roof-tile shaped (horizontal)
- Medical-grade polyurethane, soft, atraumatic, thermosensible
- Modular: 6 different types of inner cannulas
- Set includes broad and adjustable OPTIFLAUSCH® tube holder, obturator and product ID card
- Size 7-10 available in two lengths
- Colour coding Inner cannula: fenestrated/unfenestrated, standard length/short Imprint outer cannula neckflange: sieve-fenestrated/non-fenestrated





Sterilized using ethylene oxid

Do not resterilize

Keep away from sunlight

Single patient use

Consult instructions for use

United States Federal law restricts this device to sale, distribution and use by or on order of a physician or a licensed practitioner (in the US only).

CE marking identification number of the notified body

Product made in Germany

## **Order information:**

**DURATWIX® UNI-VARIO LINGO** 1 ICV + 1 ICFU, SIZE 6-10

**DURATWIX® UNI-VARIO LINGO short** 1 ICV + 1 ICFU, SIZE 7-10

When ordering, please state the size after the item number!

Size	O.D. neck flange mm	O.D. Tip mm	I.D. mm	Length mm standard	REF standard	Length mm short	REF short
6	11.9	10.3	6.0	82.0	19261-06	-	-
7	11.9	10.8	7.0	82.0	19261-07	72.0	19262-07
8	12.5	11.4	8.0	85.0	19261-08	75.0	19262-08
9	13.7	12.5	9.0	88.0	19261-09	78.0	19262-09
10	15.0	13.8	10.0	91.0	19261-10	81.0	19262-10

O.D. Tip = Outer diameter of the outer tube at the tip of the cannula · O.D. neck flange = Outer diameter behind the neck flange · I.D. = Inner diameter at the tip of the cannula · Length = Length over the outer curve

**REF 19261** 

**REF 19262** 

LINGO STATE OF STATE